



Alarm Cables-B2ca s1a,d0,a1

Alarm



Construction	
Conductor	Flexible bare Cu class 5, CEI EN 60228
Insulation	LSZH
Tape	PET
Shield	Al/PET + drain wire
Sheath	LSZH green
Printing	ECS – ALARM CABLE LSZH CEI UNEL 36762 C-4 (U ₀ =400V) WW/YY [ORDER NR] 001M – B2ca s1a,d0,a1

Electrical properties	
Nominal voltage	U ₀ /U=300/500V
Test voltage	2000V
Operating temperature	-10°C +70°C

Rules
CEI EN 60332-1-2 / CEI EN 60332-3-25 / CEI UNEL 36762 C-4 (U ₀ =400V) – CE / EN 13501-6:2018

Smart code	Item number	Section mm ²	Diameter mm.	Weight Kg/Km
B-AH-006	ALHFRS0622XBVEM01	6X0,22	5.10	24.00
B-AH-008	ALHFRS0822XBVEM01	8X0,22	5.10	26.00
B-AH-010	ALHFRS1022XBVEM01	10X0,22	5.20	29.00
B-AH-012	ALHFRS1222XBVEM01	12X0,22	5.40	31.00
B-AH-020	ALHFRS2022XBVEM01	20X0,22	7.40	78.00
B-AH-502	ALHFRS5002XBVEM01	2X0,50+2X0,22	5.10	32.00
B-AH-504	ALHFRS5004XBVEM01	2X0,50+4X0,22	5.10	38.00
B-AH-506	ALHFRS5006XBVEM01	2X0,50+6X0,22	5.30	43.00
B-AH-508	ALHFRS5008XBVEM01	2X0,50+8X0,22	5.50	50.00

B-AH-510	ALHFRS5010XBVEM01	2X0,50+10X0,22	5.90	56.00
B-AH-512	ALHFRS5012XBVEM01	2X0,50+12X0,22	6.00	62.00
B-AH-702	ALHFRS7502XBVEB05	2X0,75+2X0,22	5.10	33.00
B-AH-704	ALHFRS7504XBVEM01	2X0,75+4X0,22	5.20	39.00
B-AH-706	ALHFRS7506XBVEB05	2X0,75+6X0,22	5.40	45.00
B-AH-708	ALHFRS7508XBVEM01	2X0,75+8X0,22	6.00	53.00
B-AH-710	ALHFRS7510XBVEM01	2X0,75+10X0,22	6.20	61.00
B-AH-712	ALHFRS7512XBVEM01	2X0,75+12X0,22	6.50	69.00

} The details expressed above have to be considered as an indication.

European Cable Service S.r.L. - Tel. +39 0583 436283 - www.europeancableservice.it - info@europeancableservice.it